

# Approved product certificate

No.:05842-1

X-Module A/S, Test lab. Facility, Lilleringvej 24, 8462 Harlev

Product licenced to: X-Module A/S, Lilleringvej 14, DK-8462 Harlev J

Product manufactured by: X-Module A/S, Lilleringvej 24, DK-8462 Harlev J

Applicant of testing: Mr. Anders Jespersen  
Date of testing: 10.12.2024  
Certificate file reference: Udvikling/ SEG X15/ Test  
Date of issue: 16.12.2024  
Valid until: 16.12.2026

Test facility:



Signature:



Product description - dimensions:

- Single square truss system: "X15-SEG" (Pat.ped, EUR design)
- Dimensions: Square truss 150 x 150 mm (outer dimensions).
- Cord members: Ø 20 mm
- Bracing member: Ø 8 mm
- Truss units lengths: 0.15 - 2,4 m

Product description - materials:

- Supportive elements: Aluminium AlMgSi0,5
- Truss elements: 30% fibre reinforced composite.

Product components tested according to:

- DIN 4113; ISO 527-1/-2

Flammability:

- The products qualify for DIN 4102-B1; ISO 1210/UL94-VO

Additional information:

- Truss units assembled with connecting element (connector) or cubic connecting element (cube) is disregarded by test.
- Single individual units only.

Load data, structure:

- Allowable normal force on main cord: 250 N
- Allowable normal force on bracing members: 25 N

Load data, Truss units:

Truss length (m)	Undistributed load (Kg)	Distributed load (Kg)
0,6	100	100
1,2	100	100
1,8	100	100
2,4	75	100

- Modules must be connected to verticals in both ends
- Max. free span 7,2 m.
- Spans must be supported at both ends.
- Loads are in addition to self weight loads
- Only use standard connectors for truss.
- Load table only applies to simple beam load case.